

BCI GROUP SIZE	TYPE	CAPACITY <sup>A</sup> Minutes			CAPACITY <sup>B</sup> Amp-Hours (AH)		TERMINAL TYPE (See Below)	DIMENSIONS <sup>C</sup> Inches (mm)			WEIGHT lbs. (kg)
		@25 Amps	@56 Amps	@75 Amps	5 Hr Rate	20 Hr Rate		L	W	H <sup>D</sup>	
<b>6 VOLT DEEP CYCLE BATTERIES</b>											
GC2	T-605	383	-	105	175	210	1,3,4,5	10 3/8 (264)	7 1/8 (181)	10 7/8 (276)	58 (26)
GC2	T-105	447	-	115	185	225	1,3,4,5	10 3/8 (264)	7 1/8 (181)	10 7/8 (276)	62 (28)
GC2	T-105 Plus	447	-	115	185	225	1,2,4	10 3/8 (264)	7 1/8 (181)	10 11/16 (272)	62 (28)
GC2	T-125	488	-	132	195	240	1,3,4,5	10 3/8 (264)	7 1/8 (181)	10 7/8 (276)	66 (30)
GC2	T-125 Plus	488	-	132	195	240	1,2,4	10 3/8 (264)	7 1/8 (181)	10 11/16 (272)	66 (30)
GC2H	T-145	530	-	145	215	260	1,3,4,5	10 3/8 (264)	7 1/8 (181)	11 5/8 (295)	72 (33)
GC2H	T-145 Plus	530	-	145	215	260	1,2,4	10 3/8 (264)	7 1/8 (181)	11 1/2 (292)	72 (33)
<b>8 VOLT DEEP CYCLE BATTERIES</b>											
GC8	T-860	-	90	-	125	150	1	10 3/8 (264)	7 1/8 (181)	10 7/8 (276)	58 (26)
GC8	T-875	295	117	-	145	170	1,3,4	10 3/8 (264)	7 1/8 (181)	10 7/8 (276)	63 (29)
GC8	T-890	340	132	-	155	190	1,3,4	10 3/8 (264)	7 1/8 (181)	10 7/8 (276)	69 (31)
<b>12 VOLT DEEP-CYCLE BATTERIES</b>											
N/A	T-1260 Plus	260	90	60	113	140	1,2,4	12 7/8 (327)	7 1/8 (181)	10 11/16 (272)	78 (35)
N/A	T-1275	280	102	-	120	150	1	12 7/8 (327)	7 1/8 (181)	10 7/8 (276)	82 (37)
N/A	T-1275 Plus	280	102	-	120	150	1,2,4	12 7/8 (327)	7 1/8 (181)	10 11/16 (272)	82 (37)
<b>6 VOLT DEEP-CYCLE GEL BATTERIES</b>											
GC2	6V-GEL	394	-	-	154	189	5	10 1/4 (260)	7 1/8 (181)	10 7/8 (276)	68 (31)

- A. The number of minutes a battery can deliver when discharged at a constant rate at 80°F (27°C) and maintain a voltage above 1.75 V/cell. Capacities are based on peak performance.
- B. The amount of amp-hours (AH) a battery can deliver when discharged at a constant rate at 80°F (27°C) for the 20 Hr rate and 86°F (30°C) for the 5 Hr rate and maintain a voltage above 1.75 V/cell. Capacities are based on peak performance.
- C. Dimensions are based on maximum size. Dimensions may vary depending on type of handle or terminal.
- D. Dimensions taken from bottom of the battery to the highest point on the battery. Heights may vary depending on type of terminal.

**TERMINAL CONFIGURATIONS**



For a Trojan Master Distributor near you, call 800-423-6569 or 562-236-3000 or visit us at [www.trojanbattery.com](http://www.trojanbattery.com).