



N427-46 PE26-28, PWK28

J J H

Taper L1 Diameter



Operations affected by needle selection



Rich ← 1/8 to 1/4 Throttle → Lean

		Diameter (d-1) mm													
Taper (A) In degrees	(L1) length In mm		D=2.405	E=2.405	F=2.415	G=2.425	H=2.435	J=2.445	K=2.455	L=2.465	M=2.475	N=2.485	P=2.495	Q=2.505	S=2.525
G 2° 26'	F=22.25 J=25.40	RICH	---	---	---	---	GFH/017-610	---	GFK/017-612	---	---	---	---	---	---
		LEAN	---	---	---	---	GJH/017-615	---	GJK/017-616	---	---	---	---	---	---
H 2° 45'	F=22.25 K=25.85 L=27.20	RICH	---	---	HFF/017-617	HFG/017-618	HFH/017-619	---	HFK/017-620	---	---	---	---	---	---
		LEAN	---	---	HKF/017-650	HKG/017-651	HKH/017-652	HKJ/017-653	HKK/017-654	HKL/017-655	---	---	---	---	---
			---	---	---	HLG/017-621	HLH/017-622	HLJ/017-623	---	---	---	---	---	---	---
J 3° 00'	F=22.25 G=23.60 J=25.40	RICH	---	---	---	JFG/017-625	---	JFJ/017-626	---	JFL/017-627	---	JFN/017-051	JFP/017-628	JFQ/017-052	JFS/017-053
		LEAN	JJD/017-179	JJE/017-185	JJF/017-186	JJG/017-187	JJH/017-180	JJJ/017-188	JJK/017-189	JJL/017-181	JJM/017-630	JJN/017-182	---	JGQ/017-055	JGS/017-056
			---	---	JLF/017-631	JLG/017-632	JLH/017-633	JLJ/017-634	---	---	---	---	---	---	---
K 3° 15'	L=27.20	RICH	---	---	---	---	---	---	---	---	---	---	---	---	---
		LEAN	---	---	---	KLK/017-664	---	---	---	---	---	---	---	---	---
L 3° 33'	G=23.60 J=25.40	RICH	---	---	---	---	---	---	---	---	---	---	---	---	---
		LEAN	---	---	---	LJG/017-062	LGH/017-636	LGH/017-636	---	LGL/017-058	---	LGN/017-059	---	---	---
M 3° 50'	J=25.40 L=27.20	RICH	---	---	---	---	---	---	---	---	---	MJN/017-067	---	MJQ/017-068	MJS/017-069
		LEAN	---	---	---	---	---	---	---	MLL/017-190	---	MLN/017-191	---	MLQ/017-192	MLS/017-193

LEAN ↑ 1/4 to 3/4 Throttle ↓ RICH